

CLAIMS

1. A proton exchange membrane fuel cell comprising:
 - a membrane electrode assembly comprising a proton permeable
membrane bonded on one side to a porous anode and bonded
on the opposite side to a porous cathode;
 - a continuous supply of a borohydride anolyte and a means of flowing
the anolyte over the anode of the cell;
 - a continuous supply of a catholyte and a means of flowing the
catholyte over the cathode of the cell;
 - a first anode catalyst embedded in surface of the anode and catalyzing
the anolyte to generate hydrogen;
 - a second anode catalyst embedded in surface of the anode and
catalyzing hydrogen produced by the first anode catalyst to
generate hydrogen ions; and
 - a cathode catalyst embedded in surface of the cathode and catalyzing
the catholyte.
2. The fuel cell of claim 1, wherein hydrogen diffuses from the first anode
catalyst to the second anode catalyst without the accumulation of hydrogen
gas beyond the surfaces of the two anode catalysts.
3. The fuel cell of claim 1, wherein the first anode catalyst is selected from the
group consisting of ruthenium, rhodium, cobalt, iron, nickel, palladium,
rhenium, osmium, and platinum.
4. The fuel cell of claim 3, wherein the first anode catalyst is ruthenium.
5. The fuel cell of claim 1, wherein the second anode catalyst is selected from the
group consisting of ruthenium, rhodium, cobalt, iron, nickel, palladium,
rhenium, osmium, and platinum.
6. The fuel cell of claim 5, wherein the second anode catalyst is platinum.

7. The fuel cell of claim 1, wherein the cathode catalyst is selected from the group consisting of ruthenium, rhodium, cobalt, iron, nickel, palladium, rhenium, osmium, and platinum.
- 5 8. The fuel cell of claim 7, wherein the cathode catalyst is platinum.
9. The fuel cell of claim 1, wherein the borohydride anolyte comprises a carrier mixed with a borohydride compound.
- 10 10. The fuel cell of claim 9, wherein the borohydride anolyte carrier is an aqueous carrier.
11. The fuel cell of claim 9, wherein the borohydride anolyte carrier is a non-aqueous carrier.
- 15 12. The fuel cell of claim 9, wherein the borohydride compound is a metal borohydride salt.
13. The fuel cell of claim 12, wherein the borohydride compound is sodium borohydride.
- 20 14. The fuel cell of claim 1, wherein the catholyte is oxygen gas.
15. The fuel cell of claim 1, wherein the catholyte is air.
- 25 16. A method of obtaining electrical power through the electrochemical conversion of a continuous supply of a borohydride anolyte within a proton exchange membrane fuel cell having a membrane electrode assembly comprising a proton permeable membrane bonded on one side to a porous anode and bonded on the opposite side to a porous cathode, the method comprising the steps of:
- 30 selecting and embedding in surface of the anode a first anode catalyst to generate hydrogen by catalyzing the anolyte; and

40059693-0128007-208210-86965007

selecting and embedding in surface of the anode a second anode catalyst to generate hydrogen ions by catalyzing hydrogen produced by the first catalyst;
selecting and embedding in surface of the cathode a cathode catalyst to catalyze the catholyte;
flowing the catholyte over the cathode of the cell; and
flowing the anolyte over the anode of the cell.

17. The method of claim 16, wherein hydrogen diffuses from the first anode catalyst to the second anode catalyst without the accumulation of hydrogen gas beyond the surfaces of the two anode catalysts.
18. The method of claim 16, wherein the first anode catalyst is selected from the group consisting of ruthenium, rhodium, cobalt, iron, nickel, palladium, rhenium, osmium, and platinum.
19. The method of claim 18, wherein the first anode catalyst selected is ruthenium.
20. The method of claim 16, wherein the second anode catalyst is selected from the group consisting of ruthenium, rhodium, cobalt, iron, nickel, palladium, rhenium, osmium, and platinum.
21. The method of claim 20, wherein the second anode catalyst selected is platinum.
22. The method of claim 16, wherein the cathode catalyst is selected from the group consisting of ruthenium, rhodium, cobalt, iron, nickel, palladium, rhenium, osmium, and platinum.
23. The method of claim 22, wherein the cathode catalyst selected is platinum.
24. The method of claim 16, wherein the borohydride anolyte comprises a carrier mixed with a borohydride compound.

25. The method of claim 24, wherein the borohydride anolyte carrier is an aqueous carrier.

5 26. The method of claim 24, wherein the borohydride anolyte carrier is a non-aqueous carrier.

27. The method of claim 24, wherein the borohydride compound is a metal borohydride salt.

10

28. The method of claim 27, wherein the borohydride compound is sodium borohydride.

29. The method of claim 16, wherein the catholyte is oxygen gas.

15

30. The method of claim 16, wherein the catholyte is air.

2002235-0042